



OSIDOL

[OIL SPILL DISPERSANT]

INTRODUCTION:

OSIDOL IS PRIMARILY FORMULATED TO PERFORM AS AN OIL SPILL DISPERSANT. IT ALSO REMOVES GREASE AND DIRT FROM OIL TANKS, DECKS, SHOPS, FLOORS, ETC.

TYPE:

OSIDOL IS A BLEND OF SURFACE ACTIVE AGENTS, PARAFINS AND OTHER ORGANIC DISPERSANTS.

PHYSICAL PROPERTIES:

| | | |
|-------------------------------------|---|---|
| APPEARANCE | : | CLEAR TRANSPARENT HOMOGENOUS LIQUID |
| SPECIFIC GRAVITY AT 27 DEGREE C | : | 0.80 + 0.05 |
| VISCOSITY BROOKFIELD AT 27 DEGREE | : | 6.5 CPM |
| SPINDAL NO 1 RPM 20 | | |
| FLASH POINT COC | : | 48 DEGREE C |
| FLOW TIME AT 27 DEGREE C FORD CUP 4 | : | 11 SECONDS |
| SOLUBILITY | : | [A] SOLUABLE IN PETRO AND MINERAL SOLVENT [B] FORM EMULSION WITH WATER |

APPLICATION:

- [1] ADD OSIDOL TO WATER TO MAKE BETWEEN 10 % TO 30 % SOLUTION, DEPENDING ON CONCENTRATION REQUIRED. WET THE AREA WITH THIS SOLUTION AND THOROUGHLY SCRUB WITH BRUSH AND FINALLY RINSE WITH WATER.
- [2] WHERE THE SPILL OF OIL AND GREASE IS PROFUSE USE OSIDOL IN CONCENTRATION FORM [WITH OUT DILUTION]. SCRUB THE AREA AND RINSE WITH PLENTY OF WATER.
- [3] FOR GENERAL USE, SPRAY OSIDOL ON THE CONTAMINATED AREA AND ALLOW TO SOAK UPTO 15 MINUTES MAXIMUM. THEN WASH WITH WATER TO CLEAN THE AREA.
- [4] OSIDOL CAN ALSO BE USED FOR CLEANING TANKS.

STORAGE AND HANDLING:

USE OF HAND GLOVES, GOGGLES AND PROTECTIVE APPAREL IS RECOMMENDED.

AVOID PROLONGED AND REPEATED CONTACT WITH SKIN.

THIS IS A CHEMICAL FOR INDUSTRIAL USE ONLY.

NOT TO BE TAKEN ORALLY.

KEEP CONTAINERS CLOSED WHEN NOT IN USED AND ALWAYS AWAY FROM HEAT, SPARK, OR OPEN FLAME.