



## PRODUCT INFORMATION REPORT

<b>DESCRIPTION</b>	: 1st QUALITY PREMIUM MARINE CONTAINER CR OVERCOAT IS AN EXCELLENT SPECIALIZED ALLKYD RESIN AND ANTI CORROSIVE BINDER BASED CR PRODUCT WHICH PROVIDES A DURABLE EXTERIOR & INTERIOR PROTECTIVE COATING. IT HAS SUPER COLOR & FINISH RETENTION PROPERTIES. WHEN FULLY CURED IT FORMS AN EXTREMELY TOUGH & ABRASION RESISTANT FINISH.
<b>USES</b>	: TO BE USED AS FINISH PAINT - OVER PRIMED SURFACES FOR SUPERIOR RESULTS. IT IS SPECIALLY & SPECIFICALLY MADE FOR SHIPPING CONTAINERS OF ALL KINDS REEFER # LEASING SHIPPING REPAIR IT CAN ALSO BE USED FOR ALL METAL SURFACES INCLUDING PROJECT SITES / EQUIPMENTS. A VERY EFFECTIVE AND EXCELLENT TOP COAT.
<b>SHADES</b>	: AVAILABLE IN ALL RAL SHADES/ WHITE/BLACK
<b>PRODUCT DATA</b>	: TYPE - SINGLE PACK
<b>PACKING</b>	: 20 LTRS
<b>COMPOSITION</b>	: SPECIALIZED ALLKYD BASED RESIN WITH ANTI CORROSIVE CR BINDER SUITABLY PIGMENTED.
<b>VOLUME SOLIDS</b>	: SPECIFIC GRAVITY - VARIABLE SUPPLY VISCOSITY-
<b>POT LIFE</b>	: 6 HOURS
<b>SHELF LIFE</b>	: 12 MONTHS
<b>APPLICATION</b>	: PREFERRED SPRAY BY AIRLESS OR CONVENTIONAL METHODS. IT CAN ALSO BE APPLICABLE BY BRUSH & ROLLER RECOMMENDED DFT # 35 MICRONS WET 75 MICRONS THEORETICAL SPREADING RATE 15SQ MTR/LTR DRYING TIME
<b>TOUCH</b>	: 45 MINUTES
<b>HANDLE</b>	: 240 MINUTES



## **PRODUCT INFORMATION REPORT**

HARD	: 24 HOURS / OVERNIGHT CURING TIME OVERCOATING INTERVALS WET ON WET OR OVERNIGHT FLASH POINT 38/100
THINNER	: OUR THINNER RECOMMENDED.
FINISH	: MATT / SEMI GLOSSY AS REQUIRED
SURFACE PREPARATION	: SURFACE SHOULD BE TOTALLY DRY, AND FREE FROM RUST, GREASE, OIL, MOISTURE & LOOSE FLAKES. IF SEVERELY CORRODED SAND BLASTING RECOMMENDED.
APPLICATION	: PREFERRED AIRLESS OR CONVENTIONAL SPRAY USE 10%- 15% THINNER AS REQUIRED TO THIN DOWN RESISTANCE GUIDE SATISFACTORILY RESISTANT TO ACIDS / ALKALIS / SOLVENTS / SALT / WATER / TEMPERATURE UPTO 90 C ABRASION RESISTANT. FLEXIBILITY VERY GOOD.